

System		
Model	ADM-88V	
Version	FullHD 4.2	
Maximum connected cameras, pcs.	8	
Operating system	Embedded Linux	
System resources	Pentaplex. Simultaneous multi-channel real-time recording, playback, network operation, USB backup	
Operation modes	AHD/TVI/CVI/CVBS/IP	
Record		
Record, channels x resolution @ fps	AHD	8xAHD-H@15, 8xAHD-M@25
	AHD + IP	4xAHD-H@18+4x1080p@25
	IP	8x1080p@25+8x960p@25, 4x3.0Mp@25, 4x5.0Mp@25
Record storage	HDD, network	
Video compression	H.264(HighProfile)	
Space occupation for 25 fps/1 channel (per day)	Video:~80Gb(1080p), ~46Gb(960p), ~34Gb(720p), ~30Gb(960H), ~20Gb(D1), Audio: 0.69Gb	
Playback		
Playback archive records, channels x resolution @ fps	AHD	4xAHD-H@15, 8xAHD-M@25
	AHD + IP	4xAHD-H@18, 4x1080p@25
	IP	4x1080p@25, 4x960p@25, 4x3.0Mp@25, 2x5.0Mp@25
Backup mode	Network, USB	
Preview screen	1/4/9/16/24	
Record mode	Manual, Alarm, Motion Detection, Schedule	
Audio		
Audio compression	G.711A	
Two-way audio	+	
Network		
Network interface	RJ-45 (10/100Base-T)	
Network functions	NiP/DDNS/IPFilter/Email/NTP/UPNP/FTP/RTSP	
Languages supported	English, Russian, Arabic, French, Polish, Romanian, Hungarian, Italian, Czech	
Default IP address	DHCP (Auto)	
Username	admin	
Password	admin	
HTTP port	80	
ONVIF port	8899	
RTSP port	554	
RTSP string	rtsp://192.168.1.10:554/user=admin&password=admin&chan nel=1&stream=0.sdp?	
Control port	34567	
Configuration software	Partizan Device Manager	
Monitoring program	Partizan Device Manager, Partizan CMS, Partizan VMS	
Mobile software	Partizan Device Manager , Partizan Cloud Storage	
Protocol integration	Partizan SDK, ONVIF 2.4+	
Interface		
Display quality	1920x1080; 1440x900; 1280x1024; 1280x720; 1024x768	
Video inputs	8ch BNC	
Video outputs	1ch VGA, 1ch HDMI	
Audio inputs	1ch RCA	
Audio outputs	1ch RCA	
Alarm inputs	-	
Alarm outputs	-	
PTZ control	-	
USB	2xUSB2.0	
Internal SATA, (max. 6Tb)	1	
External SATA, (max. 6Tb)	-	
External eSATA, (max. 6Tb)	-	
Dimensions		
Size, mm	210x200x45	
Weight, g	900	
Common		
Accessories	Optical mouse, power adapter	
Power supply	DC12V, A	2.0
	PoE/Class	-
Housing material	Plastic	
Front material	Plastic	
Operating temperature, °C	0 - +55	
Warranty, years	3	