



- 5.0 Mp resolution
- IP66 rating
- SMD IR LED
- 3-Axis mounting
- ONVIF 2.4 protocol support

Your manual is here:
<http://manuals.partizan.global>



Partizan software:
<http://apps.partizan.global>



IP Camera		
Model		IPD-5SP-IR SE
Version		1.0
Image Sensor		
Sensor		1/2.7" OmniVision
Pixel Size, μm		2.8x2.8
Resolution, pixels@fps	Mainstream (max)*	PAL:2592x1944@15, 2688x1520@20, 2048x1520@25, 1920x1080@25 NTSC:2592x1944@15, 2688x1520@20, 2048x1520@30, 1920x1080@30
	Substream (max)*	PAL:640x480@20, 320x288@20, NTSC:640x480@20, 320x288@20
Day/Night mode	Auto	+
	Color	+
	Black&White	+
Sensitivity, Lux		0.01
Dynamic range WDR, dB		64.6
S/N ratio, dB		39
Video functions		AES, AGC, AWB, BLC, OSD, PrivacyMasks
Codec profile	H.264/H.265	Baseline / Main / High
Exposure mode, s	Auto	1/50-1/10000
	Manual	0.256-65.536
Bitrate Type, kb/s	Constant	1024-8192
	Variable	Worst/Worse/General/Good/Better/Best
*Attention! When you set the mainstream to the maximum fps, it may cause decreasing of fps of the substream		
Lens		
Focal length, mm		2.8
Iris, F		1.4
Angle of View, $^{\circ}$	Horizontal	89
	Vertical	58
Lens Type	Aspherical	-
	Spherical	+
Lens mount		M12
Control, Manual/Auto		-
IR LED		
Distance, m		≤ 25
Number of LEDs, pcs.		12, SMD
Beam Spread, $^{\circ}$		60
Wavelength, nm		850
IR Cut Filter, Manual/Auto		-/+
Network		
Network Interface		RJ-45 (10/100Base-T)
Network functions		DDNS/IPFilter/E-mail/NTP/UPNP/RTSP
Languages supported		English
Default IP address		DHCP (Auto)
Username		admin
Password		admin
HTTP port		80
ONVIF port		80
RTSP port		554
RTSP string	Main stream	rtsp://admin:admin@ IPaddress:port /stream1
	Substream	rtsp://admin:admin@ IPaddress:port /stream2
Control port		80
Configuration software		Web interface
Monitoring program		Partizan CMS
Mobile software (support)		-
Protocol integration		ONVIF 2.4+
Dimensions		
Size, mm	Total length	86
	Housing	$\varnothing 110 \times 86$
	Bracket	-
Weight, g		375
Common		
Power Supply	DC12V, A	0.5
	PoE Class/W	0/6
Alarm	Inputs	-
	Outputs	-
Audio	Built-in microphone	-
	Inputs	-
	Outputs	-
Memory card		-
Housing material, plastic/metal		-/+
Bracket material, plastic/metal		-
IP rating		66
IK rating		-
Operating temperature, $^{\circ}\text{C}$		-40 - +60
Warranty, years		3