



- 1.0 Mp resolution
- IP66 rating
- IR leds
- Weatherproof housing
- 3-Axis mounting
- ONVIF 2.4 protocol support
- Support mobile monitoring: iOS & Android
- Remote access to the device with Partizan NIP-2

IP Camera		
Model		IPO-1SP SE
Version		1.0
Image Sensor		
Sensor		1/4" OmniVision
Pixel Size, μm		3.0x3.0
Resolution, points@fps	Main stream	PAL:1280x720@25, 704x576@25, NTSC:1280x720@30, 704x576@30
	Sub stream	PAL:704x576@6, 320x288@6, NTSC:1280x720@6, 704x576@6
Day/Night mode		Auto/Color/Black&White
Sensitivity, Lux/Iris		Color 0.5Lux@F1.2, Black/White: 0.08 Lux@F1.2
Dynamic range WDR, dB		69
S/N ratio, dB		39
Video functions		AEC, AGS, AWB, ABF, ABL, OSD, PrivacyMasks
Codec profile	H.264	Baseline / Main / High
	Auto	1/50-1/10000
Exposure mode, s	Manual	0.256-65.536
	Constant	1024-4096
Bitrate Type, kb/s	Variable	Worst/Worse/General/Good/Better/Best
Lens		
Focal length, mm		3.6
Iris, F		1.4
Angle of View, °	Horizontal	50
	Vertical	39
lens Type	Aspherical	-
	Spherical	+
Lens mount		M12
Control		-
IR LED		
Distance, m		Up to 25
Number of LEDs, pcs.		24
Beam Spread, °		60
Wavelength, nm		850
IR Cut Filter		Auto
Network		
Network interface		RJ-45 (10/100Base-T)
Network functions		Cloud/NiP/DDNS/IPFilter/E-mail/NTP/PPPoE/UPNP/FTP/RTSP
Languages supported		English, Russian, Arabic, French, Poland, Romanian, Hungarian, Italian
Default IP address		DHCP (Auto)
Username		Admin
Password		Empty by default
HTTP port		80
ONVIF port		8899
RTSP port		554
RTSP string		rtsp://192.168.1.10:554 /user=admin&password=&channel =1&stream=0.sdp?
Control port		34567
Configuration software		Partizan Device Manager
Monitoring program		Partizan CMS, Partizan Device Manager
Mobile software(support)		Partizan Device Manager, Partizan Cloud Storage
Protocol integration		Partizan SDK, ONVIF 2.4+
Dimensions		
Size, mm	Total length	160
	Housing	Ø62x90
	Bracket	Ø65x55
Weight, g		300
Common		
Power Supply	DC12V, A	0.5
	PoE, Class/W	-
Alarm	Inputs	-
	Outputs	-
Audio		-
Memory card		-
Housing material		Metal
Bracket material		Metal
IP rating		66
IK rating		-
Operating temperature, °C		-40 - +60
Warranty, years		3