



- IP network video recorder
- 8-channel realtime record
- 5Mp support
- 1xSATA (max. 6Tb)
- Built-in POE power supply
- ONVIF 2.4 protocol support
- Support mobile monitoring: iOS & Android
- Ability to work with Partizan Cloud Storage
- Remote access to the device with Partizan NIP-2

System		
Model	NVH – 822	
Version	POE 2.0	
Maximum connected cameras, pcs.	8	
Operating system	Embedded Linux	
System resources	Pentaplex. Simultaneous multi-channel real-time recording, playback, network operation, USB backup	
Record		
Record, channels x resolution @ fps	8x5Mp@25	
Record storage	HDD, network	
Video compression	H.264(HighProfile)/H.265	
Space occupation for 25 fps/1 channel (per day)	Video:~80Gb(1080p), ~46Gb(960p), ~34Gb(720p), ~20Gb(D1), ~4.8Gb(CIF) Audio: 0.69Gb	
Playback		
Playback archive records, channels x resolution @ fps	1x5Mp@25	
Backup mode	Network, USB	
Preview screen	1/4/8	
Record mode	Manual, Alarm, Motion Detection, Schedule	
Audio		
Audio compression	G.711A	
Two-way audio	+	
Network		
Network interface	RJ-45 (10/100Base-T)	
Network functions	NiP/DDNS/IPFilter/Email/NTP/UPNP/FTP/RTSP	
Languages supported	English, Russian, Arabic, French, Polish, Romanian, Hungarian, Italian, Czech	
Default IP address	DHCP (Auto)	
Username	admin	
Password	admin	
HTTP port	80	
ONVIF port	8899	
RTSP port	554	
RTSP string	rtsp://192.168.1.10:554/user=admin&password=admin&chan nel=1&stream=0.sdp?	
Control port	34567	
Configuration software	Partizan Device Manager	
Monitoring program	Partizan Device Manager, Partizan CMS, Partizan VMS	
Mobile software	Partizan Device Manager, Partizan Cloud Storage	
Protocol integration	Partizan SDK, ONVIF 2.4+	
Interface		
Display quality	1920x1080; 1440x900; 1280x1024; 1280x720; 1024x768	
Video inputs	-	
Video outputs	1ch VGA, 1ch HDMI	
Audio inputs	-	
Audio outputs	1 ch RCA	
Alarm inputs	-	
Alarm outputs	-	
PTZ control	Control PTZ device by network	
USB	2xUSB 2.0	
Internal SATA, (max. 6Tb)	1	
External SATA, (max. 6Tb)	-	
External eSATA, (max. 6Tb)	-	
Dimensions		
Size, mm	255x236x44	
Weight, g	1200	
Common		
Accessories	Optical mouse, power adapter, IR remote	
Power supply	DC48V, A	2.5
	PoE/Class	8*RJ45/0
Housing material	Metal	
Front material	Plastic	
Operating temperature, °C	0 - +50	
Warranty, years	3	