

<b>System</b>		
Model	<b>NVT-1624</b>	
Version	POE	
Maximum connected cameras, pcs.	16	
Operating system	Embedded Linux	
System resources	Pentaplex. Simultaneous multi-channel real-time recording, playback, network operation, USB backup	
<b>Record</b>		
Record, channels x resolution @ fps	16x5Mp@25, 16x3Mp@25, 8x8Mp@25	
Record storage	HDD, network	
Video compression	H.264(HighProfile)/H.265	
Space occupation for 25 fps/1 channel (per day)	Video:~80Gb(1080p), ~46Gb(960p), ~34Gb(720p), ~20Gb(D1), ~4.8Gb(CIF) Audio: 0.69Gb	
<b>Playback</b>		
Playback archive records, channels x resolution @ fps	4x5Mp@25, 8x3Mp@25, 2x8Mp@25	
Backup mode	Network, USB	
Preview screen	1/4/8	
Record mode	Manual, Alarm, Motion Detection, Schedule	
<b>Audio</b>		
Audio compression	G.711A	
Two-way audio	+	
<b>Network</b>		
Network interface	RJ-45 (10/100/1000Base-T)	
Network functions	NiP/DDNS/IPFilter/Email/NTP/UPNP/FTP/RTSP	
Languages supported	English, Russian, Arabic, French, Polish, Romanian, Hungarian, Italian, Czech	
Default IP address	<b>DHCP (Auto)</b>	
Username	<b>admin</b>	
Password	<b>admin</b>	
HTTP port	80	
ONVIF port	8899	
RTSP port	554	
RTSP string	rtsp://192.168.1.10:554/user=admin&password=admin&channel=1&stream=0.sdp?	
Control port	34567	
Configuration software	Partizan Device Manager	
Monitoring program	Partizan Device Manager, Partizan CMS, Partizan VMS	
Mobile software	Partizan Device Manager, Partizan Cloud Storage	
Protocol integration	Partizan SDK, ONVIF 2.4+	
<b>Interface</b>		
Display quality	4K; 1920x1080; 1440x900; 1280x1024; 1280x720; 1024x768	
Video inputs	-	
Video outputs	1ch VGA, 1ch HDMI	
Audio inputs	-	
Audio outputs	1 ch RCA	
Alarm inputs	-	
Alarm outputs	-	
PTZ control	Control PTZ device by network	
USB	2xUSB 3.0	
Internal SATA, (max. 8Tb)	4	
External SATA, (max. 8Tb)	-	
External eSATA, (max. 8Tb)	-	
<b>Dimensions</b>		
Size, mm	440x400x60	
Weight, g	4000	
<b>Common</b>		
Accessories	Optical mouse, power adapter, IR remote	
Power supply	Built-in	220V, 350W
	PoE/Class	16*RJ45/0
Housing material	Metal	
Front material	Plastic	
Operating temperature, °C	0 - +50	
Warranty, years	3	