



Video calling panel Myers D300S EK HD



ENG



- Colour CMOS camera
- Resolution: AHD-M/1.3Mp
- Built-in standalone controller
- Built-in card reader
- Built-in keypad
- IP 44 rating
- Angel bracket
- IR leds
- Relay lock control

Calling video panel	
Model	D-300
Version	EK HD
Colour	Silver
Camera	
Sensor	1/3" CMOS HD
Resolution	AHD-M (1.3Mp)
Day/Night mode	Auto
Photosensitivity, Lux	0.5
Video system	PAL
Video output	1 Vpp, 75Ω
Lens	
Focal length, mm	1.9
Iris, F	1.4
Horizontal angle of view, °	130
Vertical angle of view, °	83
lens Type	Spherical
IR LED	
Distance, m	3
Number of LEDs, pcs.	3
Beam Spread, °	60
Wavelength, nm	850
Dimensions	
Size, mm	130x48x32
Weight, g	340
Controller	
Card reader standard	Mifare 1K/Keypad
Max number of users	200
Authentication method	Card/Password/Card+Password
Common	
Power	DC 12V/0.2A
Relay	NO/NC
Support monitor (intercom), pcs	1
Call button, pcs	1
Exit button, pcs	1
Housing material	Metal
Bracket material	Metal
IP rating	44
Operating temperature, °C	-40 ~ +60
Accessories	Angel bracket, mounting kit.



Attention!

- Only qualified technician should be authorized to service this equipment
- Avoid placing the device near sources of strong electromagnetic radiation.
- Do not install the device in places exposed to direct sunlight, rain, extremely high temperatures, high humidity levels, high dust levels and aggressive chemicals.
- The most appropriate place to install the device is at the level of the user's eyes.
- Prior to installation and removal of the device please make sure that the power supply is off.
- Install the device at least 30cm away from the power supply lines to avoid interference.
- Avoid ingress of moisture, foreign particles, and insects into the device enclosure.