



- AHD/TVI/CVI/CVBS camera
- Resolution 4.0 Mp
- IR LED
- IP66 rating
- 3-Axis mounting
- OSD menu

Your manual is here:
<http://manuals.partizan.global>



Partizan software:
<http://apps.partizan.global>



IP Camera			
Model		COD-631H	
Version		SuperHD v1.0	
Built-in OSD menu		+	
Operating the integrated OSD menu	Joystick on the cord	+	
	UTC controller	-	
Image Sensor			
Sensor		1/2.7" CMOS	
Pixel Size, μm		2.8x2.8	
Resolution, points@fps	PAL	AHD-H:	4Mp(2592x1520)@15fps
		TVI:	4Mp(2592x1520)@15fps
		CVI:	4Mp(2592x1520)@15fps
		Analog:	1300TVL
	NTSC	AHD-H:	4Mp(2592x1520)@15fps
		TVI:	4Mp(2592x1520)@15fps
		CVI:	4Mp(2592x1520)@15fps
		Analog:	1300TVL
Day/Night mode	Auto	+	
	Color	+	
	Black&White	+	
Sensitivity, Lux		0.01	
Video functions		AEC, AGS, AWB, BLC, HLC, OSD, PrivacyMasks	
Dynamic range WDR, dB		72	
S/N ratio, dB		48	
Video output		1Vpp, 75 Ω	
Exposure mode, s	Auto	+	
	Manual	1/50 – 1/10000, 1/60-1/10000	
Lens			
Focal length, mm		2.8	
Iris, F		1.4	
Angle of View, $^{\circ}$	Horizontal	89	
	Vertical	58	
Lens Type	Aspherical	-	
	Spherical	+	
Lens mount		M12	
Control, Manual/Auto		-	
IR LED			
Distance, m		≤ 30	
Number of LEDs, pcs.		30	
Beam Spread, $^{\circ}$		60	
Wavelength, nm		850	
IR Cut Filter, Manual/Auto		-/+	
Dimensions			
Size, mm	Total length	180	
	Housing	$\varnothing 63 \times 105$	
	Bracket	$\varnothing 55 \times 75$	
Weight, g		300	
Common			
Power Supply	DC12V, A	0.4	
Alarm	Inputs	-	
	Outputs	-	
Housing material, plastic/metal		-/+	
Bracket material, plastic/metal		-/+	
IP rating		66	
IK rating		-	
Operating temperature, $^{\circ}\text{C}$		-40 - +60	
Warranty, years		3	