Partizan ADM-88V SuperHD v7.1

EN

- Hybrid SuperHD and AHD 8 channels
- AHD/TVI/CVI/CVBS/IP support
- 1xSATA (max. 14Tb)
- ONVIF 2.4 protocol support
- Support mobile monitoring: iOS & Android
- Ability to work with Partizan Cloud Storage
- Remote access to the device with Partizan MAC

Partizan software:
http://apps.partizan.global

Your manual is here:
http://manuals.partizan.global

Documentation:
https://doc.partizan.global/sku/6631

Specification		
Model		HDVR Partizan ADM-88V
Version		SuperHD v7.1
SKU		6631
Maximum connected cameras		8 Analog or 16 IP
Operating system		Embedded Linux
Simultaneous multi-channel real-time recording		+
Playback		+
Network operation		+
USB backup		+
Operation modes		AHD/TVI/CVI/CVBS/IP
Record		
Record, channels x resolution @ fps	AHD	8x5.0M-N@12, 8x4.0M-N@15, 8xAHD-H@15
	AHD + IP	8x5M-N@12 + 4x2Mp@25
	IP	16x2.0Mp@25, 8x5.0Mp@25
Record storage, HDD*/network		+/+
Video compression		H.264/H.265
Space occupation for 25 fps/1 channel (per day)	Video H.264	~202Gb(8Mp), ~150Gb(5Mp), ~120Gb(4Mp), ~80Gb(2Mp), ~20Gb(D1)
	Video H.265	~135Gb(8Mp), ~100Gb(5Mp), ~80Gb(4Mp), ~53Gb(2Mp), ~14Gb(D1)
	Audio	0.69Gb
*Please note, HDD is not included in the kit!		
Playback		
Playback archive records, channels x resolution @ fps	AHD	2x5.0M-N@12, 2x4.0M-N@15, 2xAHD-H@15
	AHD + IP	2x5M-N@12, 2x2Mp@25
	IP	2x2.0Mp@25, 1x5.0Mp@25
Backup mode, network/USB		+/+
Preview screen		Analog 1/4/8/9, IP up to 16
Record mode	Manual	+
	Alarm	+
	Motion Detection	+
	Schedule	Regular / Motion Detection / Alarm
Audio		
Audio compression		G.711A
Two-way audio		+
Network		
Network Interface		RJ-45 (10/100Base-T)
Network functions		Partizan MAC protocol /PPPoE/NTP/Email/IPFilter/DDNS/FTP/ARSP /Alarm Server/UPNP/RTSP
Languages supported		Arabic, Czech, English, French, German, Hebrew, Hungarian, Italian, Polish, Romanian, Russian, Spanish, Ukrainian
Default IP address		**DHCP (Auto)**
Default username		**admin**
Default password		**admin**
HTTP port		80
RTSP port		554
RTSP string		rtsp://192.168.1.10:554/user=admin&password=admin&channel=1&stream=0.sdp?
Control port		34567
PTZ control protocol		+
Configuration software		Partizan (Setup Tool), Web interface (IE)
Monitoring program		Partizan
Mobile software (support)		Partizan
Protocol integration		Partizan SDK, ONVIF 2.4+ (Profile S)
Interface		
Display quality		1920x1080; 1440x900; 1280x1024; 1280x720; 1024x768
Video	Inputs	8ch BNC, IP
	Outputs	1ch VGA, 1ch HDMI
Audio	Inputs	1ch RCA
	Outputs	1ch RCA
Alarm	Inputs	-
	Outputs	-
USB		2×USB2.0
Internal SATA, pcs x max.Tb		1×14
External SATA		-

Dimensions		
Size (W×D×H) mm		250×210×42
Weight		680g
Common		
Accessories	Optical mouse	+
	Power adapter	+
	IR remote	-
Power supply	DC12V	2A
	PoE/Class	-
Housing material, plastic/metal		-/+
Front material, plastic/metal		+/-
Operating temperature, C°		0° - +55°
Warranty		3 years

*Note: the functions, interface, component parts and the working sequence of the device are subject to alteration without prior notice from the manufacturer due to updates of the device itself as well as its software