



- 2.0 Mp resolution
- IP44 rating
- C/CS mount
- Audio In/Out
- Alarm In/Out
- SD card support
- ONVIF 2.4 protocol support

IP Camera		
Model		IPB-2MP
Version		WDR POE 1.1
Image Sensor		
Sensor		1/2.7" Panasonic Progressive Scan
Pixel Size, µm		2.7x2.7
Resolution, points@fps	Main stream	PAL: 1920x1080@50, 1280x720@25, NTSC: 1920x1080@60, 1280x720@30
	Sub stream	PAL: 704x576@25, 352x288@25, NTSC: 704x576@30, 352x288@30
Day/Night mode		Auto/Color/Black&White
Sensitivity, Lux/Iris		0.01Lux@F1.4
Dynamic range WDR, dB		120
S/N ratio, dB		50
Video functions		BLC, WDR, AGC, Slow Shutter, OSD, Privacy Masks, True WDR
Codec profile	H.264/MJPEG/H.265	Baseline / Main / High
	Auto	1/25-1/10000
Exposure mode, s	Manual	0.256-65.536
	Constant	1024-8192
Bitrate Type, kb/s	Variable	Worst/Worse/General/Good/Better/Best
Lens		
Focal length, mm		-
Iris, F		-
Angle of View, °	Horizontal	-
	Vertical	-
lens Type	Aspherical	-
	Spherical	-
Lens mount		C\CS
Control		-
IR LED		
Distance, m		-
Number of LEDs, pcs.		-
Beam Spread, °		-
Wavelength, nm		-
IR Cut Filter		-
Network		
Network Interface		RJ-45 (10/100Base-T)
Network functions		DDNS/IPFilter/E-mail/NTP/PPPoE/UPNP/FTP/RTSP
Languages supported		English
Default IP address		<a href="http://192.168.1.88">http://192.168.1.88</a>
Username		admin
Password		admin
HTTP port		80
ONVIF port		2000
RTSP port		554
RTSP string	Main stream	rtsp://ip/av0_0&user=admin&password=admin
	Sub stream	rtsp://ip/av0_1&user=admin&password=admin
Control port		5000
Configuration software		Web interface
Monitoring program		Partizan CMS
Mobile software(support)		-
Protocol integration		ONVIF 2.4+
Dimensions		
Size, mm	Total length	-
	Housing	78x56x145
	Bracket	-
Weight, g		485
Common		
Power Supply	DC 12V, A	0.5
	PoE, Class/W	0/6
Alarm	Inputs	1
	Outputs	1
Audio	Inputs	1
	Outputs	1
Memory card		MicroSD(Up to 128Gb)
Housing material		Metal
Bracket material		-
IP rating		44
IK rating		-
Operating temperature, °C		+10 - +50
Warranty, years		3