



- 2.0 Mp resolution
- High sensitivity
- Smart people counting support
- Alarm input/output, Audio output
- IP66 rating
- SMD IR LED
- 3-Axis mounting
- ONVIF 2.4 protocol support
- Support mobile monitoring: iOS & Android

Your manual is here:
<http://manuals.partizan.global>



Partizan software:
<http://apps.partizan.global>



IP Camera		
Model		IPD-VF2MP-IR SE
Version		SPC
SKU		1822
Image Sensor		
Sensor		1/2.9" FullHD CMOS
Pixel Size, μm		2.9x2.9
Resolution, pixels@fps	Mainstream (max)*	PAL: 1920x1080@25, 1280x720@25, NTSC: 1920x1080@30, 1280x720@30
	Substream (max)*	PAL: 704x576@25, NTSC: 704x576@30
Day/Night mode	Auto	+
	Color	+
	Black&White	+
Sensitivity, Lux		0.01
Dynamic range WDR, dB		72
S/N ratio, dB		48
Video functions		AES, AGC, AWB, BLC, OSD, PrivacyMasks
Smart functions		People counting
Codec profile	H.264/H.265	Baseline / Main / High
Exposure mode, s	Auto	1/50-1/10000
	Manual	0.256-65.536
Bitrate Type, kb/s	Constant	1024-8192
	Variable	Worst/Worse/General/Good/Better/Best
*Attention! When you set the mainstream to the maximum fps, it may cause decreasing of fps of the substream		
Lens		
Focal length, mm		2.8-12
Iris, F		1.4
Angle of View, °	Horizontal	91
	Vertical	75
Lens Type	Aspherical	-
	Spherical	+
Lens mount		M12
Control, Manual/Auto		+/-
IR LED		
Distance, m		≤25
Number of LEDs, pcs.		18, SMD
Beam Spread, °		60
Wavelength, nm		850
IR Cut Filter, Manual/Auto		-/+
Network		
Network Interface		RJ-45 (10/100Base-T)
Network functions		Cloud/NiP/DDNS/IPFilter/E-mail/NTP/UPNP/RTSP
Languages supported		English, Russian, Arabic, French, Polish, Romanian, Hungarian, Italian, Czech
Default IP address		DHCP (Auto)
Username		admin
Password		admin
HTTP port		80
ONVIF port		2000
RTSP port		554
RTSP string		rtsp://IPaddress:port/av0_0&user=admin&password=admin
Control port		5000
Configuration software		Partizan
Monitoring program		Partizan
Mobile software (support)		Partizan
Protocol integration		Partizan SDK, ONVIF 2.4+
Dimensions		
Size, mm	Total length	107
	Housing	∅140x107
	Bracket	-
Weight, g		900
Common		
Power Supply	DC12V, A	0.5
	PoE Class/W	0/6
Alarm	Inputs	+
	Outputs	+
Audio	Built-in microphone	-
	Inputs	-
	Outputs	+
Memory card		-
Housing material, plastic/metal		-/+
Bracket material, plastic/metal		-
IP rating		66
IK rating		10
Operating temperature, °C		-40 - +60
Warranty, years		3