



- 2.0 Mp resolution
- IP66 rating
- IK10 rating
- IR LED
- 3-Axis mounting
- ONVIF 2.4 protocol support
- Audio input/output

Your manual is here:  
<http://manuals.partizan.global>



Partizan software:  
<http://apps.partizan.global>



IP Camera		
Model	IPD-VF2MP-IR	
Version	WDR	
Image Sensor		
Sensor	1/2.7" Panasonic Progressive Scan	
Pixel Size, μm	2.7x2.7	
Resolution, pixels@fps	Mainstream (max)*	PAL: 1920x1080@25, 1280x720@25, NTSC: 1920x1080@30, 1280x720@30
	Substream (max)*	PAL: 704x576@25, 352x288@25, NTSC: 704x576@30, 352x288@30
Day/Night mode	Auto	+
	Color	+
	Black&White	+
Sensitivity, Lux	0.01	
Dynamic range WDR, dB	120	
S/N ratio, dB	50	
Video functions	AES, AGC, AWB, BLC, OSD, PrivacyMasks, True WDR	
Codec profile	H.264/MJPEG/H.265	Baseline / Main / High
Exposure mode, s	Auto	1/50-1/10000
	Manual	0.256-65.536
Bitrate Type, kb/s	Constant	1024-8192
	Variable	Worst/Worse/General/Good/Better/Best
<b>*Attention! When you set the mainstream to the maximum fps, it may cause decreasing of fps of the substream</b>		
Lens		
Focal length, mm	2.8-12	
Iris, F	1.4	
Angle of View, °	Horizontal	89-26
	Vertical	58-15
Lens Type	Aspherical	-
	Spherical	+
Lens mount	M12	
Control, Manual/Auto	+/-	
IR LED		
Distance, m	≤30	
Number of LEDs, pcs.	36	
Beam Spread, °	60	
Wavelength, nm	850	
IR Cut Filter, Manual/Auto	-/+	
Network		
Network Interface	RJ-45 (10/100Base-T)	
Network functions	DDNS/IPFilter/E-mail/NTP/UPNP/RTSP	
Languages supported	English	
Default IP address	<b>http://192.168.1.88</b>	
Username	<b>admin</b>	
Password	<b>admin</b>	
HTTP port	80	
ONVIF port	2000	
RTSP port	554	
RTSP string	Main stream	rtsp://ip/av0_0&user=admin&password=admin
	Sub stream	rtsp://ip/av0_1&user=admin&password=admin
Control port	5000	
Configuration software	-	
Monitoring program	Partizan CMS	
Mobile software (support)	-	
Protocol integration	ONVIF 2.4+	
Dimensions		
Size, mm	Total length	112
	Housing	Ø119x112
	Bracket	-
Weight, g	810	
Common		
Power Supply	DC12V, A	0.8
	PoE Class/W	0/12
Alarm	Inputs	-
	Outputs	-
Audio	Built-in microphone	-
	Inputs	+
	Outputs	+
Memory card	-	
Housing material, plastic/metal	-/+	
Bracket material, plastic/metal	-	
IP rating	66	
IK rating	10	
Operating temperature, °C	-40 - +60	
Warranty, years	3	