



- 5.0 Mp resolution
- High sensitivity
- Smart functions support
- IP66 rating
- 3-Axis mounting
- ONVIF 2.4 protocol support
- Support mobile monitoring: iOS & Android
- Ability to work with Partizan Cloud Storage
- Remote access to the device with Partizan MAC

Your manual is here:  
<http://manuals.partizan.global>



Partizan software:  
<http://apps.partizan.global>



IP Camera		
Model	IPD-VF5MP-IR	
Version	Starlight v3.1 Cloud	
SKU	1714	
Image Sensor		
Sensor	1/2.7" CMOS	
Pixel Size, µm	2.0x2.0	
Resolution, pixels@fps	Mainstream (max)*	PAL: 2592x1944@15, 2560x1440@20, 1920x1080@20, NTSC: 2592x1944@15, 2560x1440@20, 1920x1080@20
	Substream (max)*	PAL: 704x576@25, NTSC: 704x576@30
Day/Night mode	Auto	+
	Color	+
	Black&White	+
Sensitivity, Lux	0.01	
Dynamic range WDR, dB	72	
S/N ratio, dB	48	
Video functions	AES, AGC, AWB, BLC, OSD, PrivacyMasks	
Smart functions	Human detection (more functions when using together with Cloud-series NVR)	
Codec profile	H.264/H.265	Baseline / Main / High
Exposure mode, s	Auto	1/50-1/10000
	Manual	0.256-65.536
Bitrate Type, kb/s	Constant	128-8192
	Variable	Worst/Worse/General/Good/Better/Best
*Attention! When you set the mainstream to the maximum fps, it may cause decreasing of fps of the substream		
Lens		
Focal length, mm	2.8-12	
Iris, F	1.4	
Angle of View, °	Horizontal	91-27
	Vertical	75-20
Lens Type	Aspherical	-
	Spherical	+
Lens mount	M12	
Control, Manual/Auto	+/-	
IR LED		
Distance, m	≤30	
Number of LEDs, pcs.	24 SMD	
Beam Spread, °	60	
Wavelength, nm	850	
IR Cut Filter, Manual/Auto	-/+	
Network		
Network interface	RJ-45 (10/100Base-T)	
Network functions	Cloud/NiP/DDNS/IPFilter/E-mail/NTP/UPNP/FTP/RTSP	
Languages supported	English, Russian, Arabic, French, Polish, Romanian, Hungarian, Italian, Czech	
Default IP address	DHCP (Auto)	
Username	admin	
Password	admin	
HTTP port	80	
ONVIF port	8899	
RTSP port	554	
RTSP string	rtsp://IPaddress:port/user=admin&password=admin&channel=1&stream=0.sdp?	
Snapshot capture link	http://IPaddress/webcapture.jpg?command=snap&channel=1&user=admin&password=admin	
Control port	34567	
Configuration software	Partizan (Setup Tool), Partizan Device Manager	
Monitoring program	Partizan	
Mobile software (support)	Partizan	
Protocol integration	Partizan SDK, ONVIF 2.4+	
Dimensions		
Size, mm	Total length	90
	Housing	Ø130x90
	Bracket	-
Weight, g	700	
Common		
Power Supply	DC12V, A	0.5
	PoE Class/W	0/6
Alarm	Inputs	-
	Outputs	-
Audio	Built-in microphone	-
	Inputs	+ (only for passive microphone)
	Outputs	-
Memory card	-	
Housing material, plastic/metal	-/+	
Bracket material, plastic/metal	-	
IP rating	66	
IK rating	-	
Operating temperature, °C	-40 - +60	
Warranty, years	3	