



- 5.0 Mp resolution
- IP44 rating
- ONVIF 2.4 protocol support

IP Camera		
Model		IPF-5SP
Version		POE
Image Sensor		
Sensor		1/2.5" Aptina
Pixel Size, μm		2.2x2.2
Resolution, points@fps	Main stream	PAL:2592x1944@25, NTSC:2592x1944@30
	Sub stream	PAL:704x576@25, NTSC:704x576@30
Day/Night mode		Auto/Color/Black&White
Sensitivity, Lux/Iris		Color 0.15Lux@F1.2, Black/White: 0.08 Lux@F1.2
Dynamic range WDR, dB		69
S/N ratio, dB		44
Video functions		AEC, AGS, AWB, ABF, ABL, OSD, PrivacyMasks
Codec profile	H.264	Baseline / Main / High
Exposure mode, s	Auto	1/50-1/10000
	Manual	0.256-65.536
Bitrate Type, kb/s	Constant	1024-8192
	Variable	Worst/Worse/General/Good/Better/Best
Lens		
Focal length, mm		1.16
Iris, F		2.0
Angle of View, °	Horizontal	180
	Vertical	180
lens Type	Aspherical	-
	Spherical	+
Lens mount		M12
Control		-
IR LED		
Distance, m		-
Number of LEDs, pcs.		-
Beam Spread, °		-
Wavelength, nm		-
IR Cut Filter		Auto
Network		
Network Interface		RJ-45 (10/100Base-T)
Network functions		DDNS/IPFilter/E-mail/NTP/PPPoE/UPNP/FTP/RTSP
Languages supported		English, Russian, Arabic, French, Poland, Romanian, Hungarian, Italian
Default IP address		DHCP (Auto)
Username		admin
Password		Empty by default
HTTP port		80
ONVIF port		8899
RTSP port		554
RTSP string		rtsp://192.168.1.10:554 /user=admin&password=&channel =1&stream=0.sdp?
Control port		34567
Configuration software		-
Monitoring program		Partizan CMS
Mobile software		-
Protocol integration		Partizan SDK, ONVIF 2.4+
Dimensions		
Size, mm	Total length	-
	Housing	ø150x55
	Bracket	-
Weight, g		500
Common		
Power Supply	DC 12V, A	0.5
	PoE, Class/W	0/6
Alarm	Inputs	-
	Outputs	-
Audio	Inputs	+
	Outputs	+
Memory card		MicroSD(Up to 64Gb)
Housing material		Plastic
Bracket material		-
IP rating		44
IK rating		-
Operating temperature, °C		+10 - +50
Warranty, years		3