



- 1.0 Mp resolution
- Pan and Tilt control
- IR leds
- IP44 rating
- ONVIF protocol support
- iOS & Android Free Software
- Free Surveillance software included

IP Camera		
Model		IPH-1SP-IR
Version		-
Image Sensor		
Sensor		1/4" OmniVision
Pixel Size, μm		3.0x3.0
Resolution, points@fps	Main stream	PAL:1280x720@25, 704x576@25, NTSC:1280x720@30, 704x576@30
	Sub stream	PAL:704x576@25, 320x288@25, NTSC:704x576@30, 320x288@30
Day/Night mode		Auto/Color/Black&White
Sensitivity, Lux/Iris		Color 0.5Lux@F1.2, Black/White: 0.08 Lux@F1.2
Dynamic range WDR, dB		69
S/N ratio, dB		39
Video functions		AES, AGC, AWB, BLC, OSD, DWDR, PrivacyMasks
Codec profile	H.264	Baseline / Main / High
Exposure mode, s	Auto	1/50-1/10000
	Manual	0.256-65.536
Bitrate Type, kb/s	Constant	1024-5120
	Variable	Worst/Worse/General/Good/Better/Best
Lens		
Focal length, mm		3.6
Iris, F		1.2
Angle of View, °	Horizontal	59
	Vertical	40
lens Type	Aspherical	-
	Spherical	+
Lens mount		M12
Control	Pan, °	355
	Tilt, °	120
IR LED		
Distance, m		Up to 10
Number of LEDs, pcs.		11
Beam Spread, °		60
Wavelength, nm		850
IR Cut Filter		Auto
Network		
Network Interface		RJ-45 (10/100Base-T)
Wireless LAN(WiFi)		+
Network functions		Cloud/NiP/DDNS/IPFilter/E-mail/NTP/UPNP/FTP/RTSP
Browser supported		Internet Explorer, Opera, Mozilla Firefox, Google Chrome
Languages supported		English, Russian, Arabic, French, Poland, Romanian, Hungarian, Italian
Default IP address		DHCP (Auto)
Username		admin
Password		admin
HTTP port		80
ONVIF port		8899
RTSP port		554
RTSP string		rtsp://192.168.1.10:554 /user=admin&password=&channel =1&stream=0.sdp?
Control port		34567
Configuration software		Partizan Device Manager
Monitoring program		Partizan Device Manager, Partizan CMS, Partizan VMS
Mobile software		Partizan Device Manager, Partizan Cloud Storage
Protocol integration		Partizan SDK, ONVIF 2.4+
Dimensions		
Size, mm	Total length	148
	Housing	Ø128x148
	Bracket	-
Weight, g		360
Common		
Power Supply	DC 5V, A	1
	PoE, Class/W	-
Alarm	Inputs	+
	Outputs	+
Audio	Inputs	Built-in microphone
	Outputs	-
Memory card		MicroSD(Up to 128Gb)
Accessories		2.5 meters LAN cable, 2.5 meters power adpter
Housing material		Plastic
Bracket material		Plastic
IP rating		44
IK rating		-
Operating temperature, °C		+10 - +55
Warranty, years		3