Partizan Cloud robot (IPH-4SP-IR)

ENG

- 4.0 Mp resolution
- Built-in microphone and speaker
- MicroSD card support
- Pan and Tilt control
- IR + White LED + Smart Detection, 24/7 Full Colour
- Wireless connect
- ONVIF 2.4 protocol support
- Support mobile monitoring: iOS & Android
- Ability to work with Partizan Cloud Storage
- Remote access to the device with Partizan MAC

Your manual is here:
http://manuals.partizan.global

Partizan software:
http://apps.partizan.global

IP Camera		
Model		IPH-4SP-IR
Version		-
SKU		4334
Image Sensor		
Sensor		1/2.7" FullHD CMOS
Pixel Size, µm		3.0x3.0
Resolution, pixels@fps	Mainstream (max)*	PAL: 4Mp@12 NTSC: 4Mp@12
	Substream (max)*	PAL: 800x448@12 NTSC: 800x448@12
Day/Night mode	Auto	+
	Color	+
	Black&White	+
Sensitivity, Lux		0.01
Dynamic range WDR, dB		72
S/N ratio, dB		48
Video functions		AES, AGC, AWB, BLC, OSD, PrivacyMasks
Codec profile	H.264/H.265	Baseline / Main / High
Exposure mode, s	Auto	1/50-1/10000
	Manual	0.256-65.536
Bitrate Type, kb/s	Constant	1024-8192
	Variable	Worst/Worse/General/Good/Better/Best
*Attention! When you set the mainstream to the maximum fps, it may cause decreasing of fps of the substream		
Lens		
Focal length, mm		3.6
Iris, F		1.2
Angle of View, °	Horizontal	89
	Vertical	58
Lens Type	Aspherical	-
	Spherical	+
Lens mount		M12
Control	Pan, °	350
	Tilt, °	90
IR LED		
Distance, m		≤15
Number of LEDs, pcs.		4 IR LED + 4 White LED
Beam Spread, °		60
Wavelength, nm		850
IR Cut Filter, Manual/Auto		-/+
Network		
Network Interface		-
Wireless LAN Standard / Frequency, Ghz		802.11(b/g/n) / 2.4
Supported encryption type	AES	+
	TKIP	+
	AES+TKIP	-
Network functions		Partizan MAC protocol/IPFilter/E-mail/NTP/UPNP/RTSP
Languages supported		English, Russian, Arabic, French, Polish, Romanian, Hungarian, Italian, Czech
Default IP address		**DHCP (Auto)**
Username		**admin**
Password		**admin**
HTTP port		80
ONVIF port		8899
RTSP port		554
RTSP string		rtsp://IPaddress:port/user=admin&password=admin&channel=1&stream=0.sdp?
Snapshot capture link		http://IPaddress/webcapture.jpg?command=snap&channel=1&user=admin&password=admin
Control port		34567
Configuration software		Partizan (Setup Tool), Partizan Device Manager
Monitoring program		Partizan
Mobile software (support)		Partizan
Protocol integration		Partizan SDK, ONVIF 2.4+
Dimensions		
Size, mm	Total length	103
	Housing	Ø73x103
	Bracket	-
Weight, g		500
Common		
Power Supply	DC5V, A	1.5
	PoE Class/W	-
Alarm	Inputs	-
	Outputs	-
Audio	Built-in microphone	+
	Built-in speaker	+
Memory card		MicroSD (≤128Gb)
Accessories		Power supply 5V/1.6A with cable 3m
Housing material, plastic/metal		+/-
Bracket material, plastic/metal		-
IP rating		44
IK rating		-
Operating temperature, °C		+10 - +50
Warranty, years		3