



- WiFi IP camera
- 1.0 Mp resolution
- IP66 rating
- Weatherproof housing
- IR leds
- 3-Axis mounting

IP Camera		
Model		IPO-1SP
Version		Kit
Image Sensor		
Sensor		1/4" SOI
Pixel Size, μm		3.0x3.0
Resolution, points@fps	Main stream	PAL: 1280x720@25, 704x576@25, NTSC: 1280x720@30, 704x576@30
	Sub stream	PAL:704x576@25, 320x288@25, NTSC:704x576@30, 320x288@30
Day/Night mode		Auto/Color/Black&White
Sensitivity, Lux/Iris		0.01
Dynamic range WDR, dB		69
S/N ratio, dB		39
Video functions		AEC, AGS, AWB, ABF, BLC, OSD, PrivacyMasks
Codec profile	H.264	Baseline / Main / High
Exposure mode, s	Auto	1/50-1/10000
	Manual	0.256-65.536
Bitrate Type, kb/s	Constant	1024-8192
	Variable	Worst/Worse/General/Good/Better/Best
Lens		
Focal length, mm		3.6
Iris, F		1.4
Angle of View, °	Horizontal	48
	Vertical	37
lens Type	Aspherical	-
	Spherical	+
Lens mount		M12
Control		-
IR LED		
Distance, m		Up to 30
Number of LEDs, pcs.		3 array LED
Beam Spread, °		60
Wavelength, nm		850
IR Cut Filter		Auto
Network		
Network Interface		RJ-45 (10/100Base-T)
WiFi standart/Frequency,GHz		802.11(b/g/n) / 2.4
Network functions		Cloud/NiP/DDNS/IPFilter/E-mail/NTP/UPNP/RTSP
Languages supported		English, Russian, Arabic, French, Poland, Romanian, Hungarian, Italian
Default IP address		DHCP (Auto)
Username		admin
Password		Empty by default
HTTP port		80
ONVIF port		-
RTSP port		-
RTSP string		-
Control port		8880
Configuration software		-
Monitoring program		Partizan WiFi KIT CMS
Mobile software		Partizan Wifi KIT
Protocol integration		-
Dimensions		
Size, mm	Total length	159
	Housing	Ø82x159
	Bracket	Ø85
Weight, g		470
Common		
Power Supply	DC12V, A	0.5
	PoE, Class/W	-
Audio		-
Housing material		Metal
Bracket material		Metal
IP rating		66
IK rating		-
Operating temperature, °C		-40 - +60
Warranty, years		3