Partizan Cloud bullet (IPO-5SP WiFi FADA)

ENG

- 5.0 Mp resolution
- High sensitivity
- Built-in microphone and speaker
- Built-in alarm red & blue flashing lights
- MicroSD card support
- Smart functions support
- IP67 rating
- IR + White LED + Smart Detection, 24/7 Full Colour
- 3-Axis mounting
- ONVIF 2.4 protocol support
- Support mobile monitoring: iOS & Android
- Ability to work with Partizan Cloud Storage
- Remote access to the device with Partizan MAC

IP Camera		
Model		IPO-5SP
Version		WiFi FADA
SKU		4473
Image Sensor		
Sensor		1/2.8" CMOS
Pixel Size, µm		2.9x2.9
Resolution, pixels@fps	Mainstream (max)*	PAL: 5Mp@20, NTSC: 5Mp@20
	Substream (max)*	PAL:640x360@25, NTSC: 640x360@30
Day/Night mode	Auto	+
	Color	+
	Black&White	+
Sensitivity, Lux		0.001
Dynamic range WDR, dB		72
S/N ratio, dB		52
Video functions		AES, AGC, AWB, BLC, OSD, PrivacyMasks
Smart functions in camera		Human detection, Face Detection
Smart functions when using together with Cloud-series NVR		Human detection / Human Perimeter Intrusion Detection / Human Line Crossing Detection
Codec profile	H.264	Baseline / Main / High
Exposure mode, s	Auto	1/50-1/10000
	Manual	0.256-65.536
Bitrate Type, kb/s	Constant	1024-8192
	Variable	Worst/Worse/General/Good/Better/Best
*Attention! When you set the mainstream to the maximum fps, it may cause decreasing of fps of the substream		
Lens		
Focal length, mm		2.8
Iris, F		1.6
Angle of View, °	Horizontal	89
	Vertical	58
Lens Type	Aspherical	-
	Spherical	+
Lens mount		M12
Control, Manual/Auto		-
Night Vision Range		
Distance, m		≤30
Number of LEDs, pcs.		2 IR LED + 2 White LED
Beam Spread, °		60
Wavelength, nm		850
IR Cut Filter, Manual/Auto		-/+
Network		
Network Interface		RJ-45 (10/100Base-T)
Wireless LAN Standard / Frequency, Ghz		802.11(b/g/n) / 2.4
Supported encryption type	AES	+
	TKIP	+
	AES+TKIP	-
Network functions		Partizan MAC protocol/DDNS/IPFilter/E-mail/NTP/UPNP/RTSP
Languages supported		English, Russian, Arabic, French, Polish, Romanian, Hungarian, Italian, Czech
Default IP address		**DHCP (Auto)**
Username		**admin**
Password		**admin**
HTTP port		80
ONVIF port		8899
RTSP port		554
RTSP string		rtsp://IPaddress:port/user=admin&password=admin&channel=1&stream=0.sdp?
Snapshot capture link		http://IPaddress/webcapture.jpg?command=snap&channel=1&user=admin&password=admin
Control port		34567
Configuration software		Partizan (Setup Tool), Partizan Device Manager
Monitoring program		Partizan
Mobile software (support)		Partizan
Protocol integration		Partizan SDK, ONVIF 2.4+
Dimensions		
Size, mm	Total length	190
	Housing	66x60x110
	Bracket	66x66x80
Weight, g		450
Common		
Power Supply	DC12V, A	0.6
	PoE Class/W	-
Alarm		Built-in red & blue flashing lights
Audio	Built-in microphone	+
	Built-in speaker	+
Memory card		MicroSD (≤512Gb)
Accessories		Power supply 12V/1A, 2.5m LAN cable
Housing material, plastic/metal		-/+
Bracket material, plastic/metal		-/+
IP rating		67
IK rating		-
Operating temperature, °C		-40 - +60
Warranty, years		3

Your manual is here:
http://manuals.partizan.global

Partizan software:
http://apps.partizan.global