



- 2.0 Mp resolution
- True WDR technology
- IP66 rating
- IK10 rating
- IR LED up to 60m
- ONVIF 2.4 protocol support

Your manual is here:
<http://manuals.partizan.global>



Partizan software:
<http://apps.partizan.global>



IP Camera		
Model		IPO-VF2MP
Version		WDR v1.0
Image Sensor		
Sensor		1/2.7" Panasonic Progressive Scan
Pixel Size, µm		2.7x2.7
Resolution, pixels@fps	Mainstream (max)*	PAL: 1920x1080@25, 1280x720@25, NTSC: 1920x1080@30, 1280x720@30
	Substream (max)*	PAL: 704x576@25, 352x288@25, NTSC: 704x576@30, 352x288@30
Day/Night mode	Auto	+
	Color	+
	Black&White	+
Sensitivity, Lux		0.01
Dynamic range WDR, dB		120
S/N ratio, dB		50
Video functions		AES, AGC, AWB, BLC, OSD, PrivacyMasks, True WDR
Codec profile	H.264/MJPEG/H.265	Baseline / Main / High
Exposure mode, s	Auto	1/50-1/10000
	Manual	0.256-65.536
Bitrate Type, kb/s	Constant	1024-8192
	Variable	Worst/Worse/General/Good/Better/Best
*Attention! When you set the mainstream to the maximum fps, it may cause decreasing of fps of the substream		
Lens		
Focal length, mm		2.8-12
Iris, F		1.4
Angle of View, °	Horizontal	82-24
	Vertical	55-15
Lens Type	Aspherical	-
	Spherical	+
Lens mount		M12
Control, Manual/Auto		+/-
IR LED		
Distance, m		≤60
Number of LEDs, pcs.		8 array LED
Beam Spread, °		60
Wavelength, nm		850
IR Cut Filter, Manual/Auto		-/+
Network		
Network Interface		RJ-45 (10/100Base-T)
Network functions		DDNS/IPFilter/E-mail/NTP/UPNP/RTSP
Languages supported		English
Default IP address		http://192.168.1.88
Username		admin
Password		admin
HTTP port		80
ONVIF port		2000
RTSP port		554
RTSP string	Main stream	rtsp://ip/av0_0&user=admin&password=admin
	Sub stream	rtsp://ip/av0_1&user=admin&password=admin
Control port		5000
Configuration software		-
Monitoring program		Partizan CMS
Mobile software (support)		-
Protocol integration		ONVIF 2.4+
Dimensions		
Size, mm	Total length	280.5
	Housing	Ø84x152.5
	Bracket	Ø84x128
Weight, g		750
Common		
Power Supply	DC12V, A	0.8
	PoE Class/W	0/12
Alarm	Inputs	-
	Outputs	-
Audio	Built-in microphone	-
	Inputs	-
	Outputs	-
Memory card		-
Housing material, plastic/metal		-/+
Bracket material, plastic/metal		-/+
IP rating		66
IK rating		10
Operating temperature, °C		-40 - +60
Warranty, years		3