



- IP network video recorder
- 16-channel realtime record
- 8Mp (4K) support
- 2xSATA (max. 8Tb)
- Alarm I/O support

Your manual is here:

<http://manuals.partizan.global>



Partizan software:

<http://apps.partizan.global>



System		
Model	NVH-1622	
Version	PRO	
Maximum connected cameras, pcs. (max/min resolution)	16	
Operating system	Embedded Linux	
Simultaneous multi-channel real-time recording	+	
Playback	+	
Network operation	+	
USB backup	+	
Record		
Record, channels x resolution @ fps	16x4K@25, 16x5.0Mp@25, 16x2.0Mp (1920x1080)@25, 16x1.3Mp (1280x960)@25, 16x1.0Mp (1280x720)@25	
Record storage, HDD*/network	+/+	
Video compression	H.264/H.265	
Space occupation for 25 fps/1 channel (per day)	Video ~80Gb(1080p), ~46Gb(960p), ~34Gb(720p), ~20Gb(D1), ~4.8Gb(CIF) Audio 0.69Gb	
*Please note, HDD is not included in the kit!		
Playback		
Playback archive records, channels x resolution @ fps	1x4K@25, 1x5.0Mp@25, 4x2.0Mp (1920x1080)@25, 4x1.3Mp (1280x960)@25, 8x1.0Mp (1280x720)@25	
Backup mode, network/USB	+/+	
Preview screen	1/4/9/16	
Record mode	Manual	+
	Alarm	+
	Motion Detection	+
	Schedule	+
Audio		
Audio compression	G.711A	
Two-way audio	+	
Network		
Network Interface	RJ-45 (10/100/1000Base-T)	
Network functions	DHCP, PPPOE, DDNS, SMTP, SNTP, FTP, UPnP, P2P	
Languages supported	English	
Default IP address	<b>192.168.1.10</b>	
Default username	<b>admin</b>	
Default password	<b>123456</b>	
HTTP port	80	
RTSP port	554	
RTSP string	rtsp://admin:admin@192.168.33.41:554/H.264?ch=1&subtype=1	
Control port	8000	
Configuration software	Partizan (Setup Tool), Web interface (IE)	
Monitoring program	Partizan, Partizan CMS PRO	
Mobile software (support)	Partizan	
Protocol integration	Onvif 2.4+	
Interface		
Display quality	4K/5MP/3MP/1080P/960P/720P	
Video	Inputs	-
	Outputs	1ch HDMI, 1ch VGA
Audio	Inputs	1ch RCA
	Outputs	1ch RCA
Alarm	Inputs	8
	Outputs	4
PTZ control, port/protocol support	Network, RS-485	
USB	2xUSB2.0	
Internal SATA, pcs x max.Tb	2x8	
External SATA, pcs x max.Tb	-	
External eSATA, pcs x max.Tb	-	
HDD operation mode	Single HDD	
Smart Functions		
Channels / Functions	-	
Dimensions		
Size, mm	360x262x48	
Weight, g	2300	
Common		
Accessories	Optical mouse	+
	Power adapter	+
	IR remote	+
Power supply	12V/3.3A	
PoE/Class	-	
Housing material, plastic/metal	-/+	
Front material, plastic/metal	+/-	
Operating temperature, °C	0 - +50	
Warranty, years	3	