



- IP network video recorder
- 8-channel realtime record
- 8Mp (4K) support
- 1xSATA (max. 8Tb)
- Built-in POE power supply
- Smart functions support

Your manual is here:

<http://manuals.partizan.global>



Partizan software:

<http://apps.partizan.global>



System		
Model		NVH-852
Version		POE PRO
Maximum connected cameras, pcs. (max/min resolution)		8
Operating system		Embedded Linux
Simultaneous multi-channel real-time recording		+
Playback		+
Network operation		+
USB backup		+
Record		
Record, channels x resolution @ fps		8x4K@25, 8x5.0Mp@25, 8x2.0Mp (1920x1080)@25, 8x1.3Mp (1280x960)@25, 8x1.0Mp (1280x720)@25
Record storage, HDD*/network		+/+
Video compression		H.264/H.265
Space occupation for 25 fps/1 channel (per day)	Video	~80Gb(1080p), ~46Gb(960p), ~34Gb(720p), ~20Gb(D1), ~4.8Gb(CIF)
	Audio	0.69Gb
*Please note, HDD is not included in the kit!		
Playback		
Playback archive records, channels x resolution @ fps		1x4K@25, 1x5.0Mp@25, 8x2.0Mp (1920x1080)@25, 8x1.3Mp (1280x960)@25, 8x1.0Mp (1280x720)@25
Backup mode, network/USB		+/+
Preview screen		1/4/8
Record mode	Manual	+
	Alarm	+
	Motion Detection	+
	Schedule	+
Audio		
Audio compression		G.711A
Two-way audio		+
Network		
Network Interface		RJ-45 (10/100Base-T)
Network functions		DHCP, PPPOE, DDNS, SMTP, SNTP, FTP, UPnP, P2P
Languages supported		English
Default IP address		192.168.1.10
Default username		admin
Default password		123456
HTTP port		80
RTSP port		554
RTSP string		rtsp://admin:admin@192.168.33.41:554/H.264?ch=1&subtype=1
Control port		8000
Configuration software		Partizan (Setup Tool), Web interface (IE)
Monitoring program		Partizan, Partizan CMS PRO
Mobile software (support)		Partizan
Protocol integration		Onvif 2.4+
Interface		
Display quality		4K/5MP/3MP/1080P/960P/720P
Video	Inputs	-
	Outputs	1ch HDMI, 1ch VGA
Audio	Inputs	1ch RCA
	Outputs	1ch RCA
Alarm	Inputs	-
	Outputs	-
PTZ control, port/protocol support		Network
USB		2xUSB2.0
Internal SATA, pcs x max.Tb		1x8
External SATA, pcs x max.Tb		-
External eSATA, pcs x max.Tb		-
HDD operation mode		Single HDD
Smart Functions		
Channels / Functions		1ch Face Detection or 2ch Intrusion Detection (for resolution up to 2MP)
Dimensions		
Size, mm		215x235x45
Weight, g		1700
Common		
Accessories	Optical mouse	+
	Power adapter	+
	IR remote	-
Power supply		DC 48V 1.875A
PoE/Class		8*RJ45/0
Housing material, plastic/metal		-/+
Front material, plastic/metal		+/-
Operating temperature, °C		0 - +50
Warranty, years		3