



- 24 PoE + 4 Uplink 10/100/1000M ports + 2 SFP port switch
- Supports IEEE802.3, IEEE802.3u, IEEE802.3x, IEEE802.3af/at, store and forward
- With DIP switch supports 10M up to 250m transmission distance via cat 6 cable
- LED indicators for monitoring power, link, activity and speed
- Compatible with 1U Rack-mount installation
- Circuit protection prevents power interference between ports
- Detects PoE power device automatically

PoE Switch		
Model	PSW-24	
Version	-	
PoE ports	24*10/100M	
Uplink ports	4*10/100/1000M	
SFP ports	2	
Bandwidth, Gbps	16.8	
Mac table size	4K	
Forwarding Mode	Store and forward	
Cache, Kb	4096	
General		
Network Protocols	IEEE 802.3i 10BASE-T; IEEE 802.3u 100BASE-TX; IEEE 802.3x Flow Control; IEEE 802.1af DTE Power via MDI; IEEE 802.3af/at	
PoE port modes	Normal(A)	24 ports support PoE
	VLAN(V)	24 ports VLAN, each port separately connects with uplink ports
	Extend(S)	24 ports extend link distance up to 250m
PoE port Power	Each port	15.4W/30W
	Total	450W
PoE standards	IEEE 802.3af/at	
Port Lightning Protection modes	General	6KV
	Differential	2KV
	ESD	15KV
Power Pin Assignment	Mode A, 1/2(+), 3/6(-)	
Dimensions		
Size, mm	440x200x45	
Weight, g	2820	
Common		
Power	AC100-240V 50/60Hz	
Casing material plastic/metal	-/+	
Color	Black	
Rack-mount installation	+	
Accessories	Power plug	+
	Mounting rails	+
Operating temperature, °C	-20 - +55	
Warranty, years	3	

Your manual is here:  
<http://manuals.partizan.global>



Partizan software:  
<http://apps.partizan.global>



### Connection diagram:

