



- 4 PoE + 2 Uplink 10/100M ports switch
- Supports IEEE802.3, IEEE802.3u, IEEE802.3x, IEEE802.3af/at, store and forward
- With DIP switch supports 10M up to 250m transmission distance via cat 6 cable
- LED indicators for monitoring power, link, activity and speed
- Compatible with 1U Rack-mount installation
- Circuit protection prevents power interference between ports
- Detects PoE power device automatically

PoE Switch		
Model	PSW-4	
Version	-	
PoE ports	4*10/100M	
Uplink ports	2*10/100M	
Bandwidth, Gbps	1.6	
Mac table size	1K	
Forwarding Mode	Store and forward	
Cache, Kb	448	
General		
Network Protocols	IEEE 802.3i 10BASE-T; IEEE 802.3u 100BASE-TX; IEEE 802.3x Flow Control; IEEE 802.1af DTE Power via MDI; IEEE 802.3af/at	
PoE port modes	Normal(A)	4 ports support PoE
	VLAN(V)	4 ports VLAN, each port separately connects with uplink ports
	Extend(S)	4 ports extend link distance up to 250m
PoE port Power	Each port	15.4W/30W
	Total	75W
PoE standards	IEEE 802.3af/at	
Port Lightning Protection modes	General	6KV
	Differential	2KV
	ESD	15KV
Power Pin Assignment	Mode A, 1/2(+), 3/6(-), Mode B, 4/5(+), 7/8(-)	
Dimensions		
Size, mm	139.6x139.6x29.6	
Weight, g	800	
Common		
Power	AC100-240V 50/60Hz	
Casing material plastic/metal	-/+	
Color	Black	
Rack-mount installation	+	
Accessories	Power plug	+
	Mounting rails	-
Operating temperature, °C	-20 - +55	
Warranty, years	3	

Your manual is here:
<http://manuals.partizan.global>



Partizan software:
<http://apps.partizan.global>



Connection diagram:

