



- 8x10/100/1000M PoE + 2xUplink 1000M SFP ports switch
- Supports IEEE802.3, IEEE802.3u, IEEE802.3ab, IEEE802.3z, IEEE802.3x, IEEE802.3af/at, store and forward
- With DIP switch supports 10M up to 250m transmission distance via cat 6 cable
- LED indicators for monitoring power, mode, link and data
- Circuit protection prevents power interference between ports
- Detects PoE power device automatically

PoE Switch		
Model	PSW-8	
Version	v1.2 SFP	
PoE ports	8*10/100/1000M	
Uplink ports	2*1000M	
Bandwidth, Gbps	20	
Mac table size	2K	
Forwarding Mode	Store and forward	
Cache, Kb	2048	
General		
Network Protocols	IEEE 802.3i 10BASE-T; IEEE 802.3u 100BASE-TX; IEEE 802.3ab 1000BASE-TX; IEEE 802.3z 1000BASE-TX; IEEE 802.3x Flow Control; IEEE 802.1af DTE Power via MDI; IEEE 802.3af/at	
Optical transmission distance, km	Multi Mode Fiber: 850nm, 1310nm	0.55, 2
	Single Mode Fiber: 1310nm, 1550nm	20, 40, 60, 80, 100, 120
PoE port modes	Extend ON	ports #7-8 extend link distance up to 250m 10M
	Extend OFF	Normal mode, all port can communicate with each other
PoE port Power	Each port	15.4W/30W
	Total	96.2W
PoE standards	IEEE 802.3af/at	
Power Pin Assignment	Mode A, 1/2(+), 3/6(-), Mode B, 4/5(+), 7/8(-)	
Dimensions		
Size, mm	268x181x44	
Weight, g	1100	
Common		
Power	AC100-240V 50/60Hz	
Casing material plastic/metal	-/+	
Color	Black	
Rack-mount installation	-	
Accessories	Power plug	+
	Mounting rails	-
Operating temperature, °C	-20 - +55	
Warranty, years	3	

Your manual is here:  
<http://manuals.partizan.global>



Partizan software:  
<http://apps.partizan.global>



Connection diagram:

