



- WiFi IP network video recorder
- 4-channel realtime record
- 2.0 Mp support
- 1xSATA (max. 4Tb)
- Support mobile monitoring: iOS & Android

| System | |
|---|--|
| Model | Outdoor Wireless Kit 2MP 4xIP |
| Version | - |
| Maximum connected cameras, pcs. | 4 |
| Operating system | Embedded Linux |
| System resources | Pentaplex. Simultaneous multi-channel real-time recording, playback, network operation, USB backup |
| WiFi operation distance (open space), m | Up to 100 |

| NVR | | |
|---|--|------|
| Record | | |
| Record, channels x resolution @ fps | 4x2.0Mp@25, 4x1.3Mp@25, 4x1.0Mp@25 | |
| Record storage | HDD, network | |
| Video compression | H.264(HighProfile) | |
| Space occupation for 25 fps/1 channel (per day) | Video: ~130Gb(5Mp), ~100Gb(3Mp), ~80Gb(1080p), ~46Gb(960p), ~34Gb(720p), ~20Gb(D1), ~4.8Gb(CIF) Audio: 0.69Gb | |
| Playback | | |
| Playback archive records, channels x resolution @ fps | 4x2.0Mp@25, 4x1.3Mp@25, 4x1.0Mp@25 | |
| Backup mode | Network, USB | |
| Preview screen | 1/4 | |
| Record mode | Manual, Alarm, Motion Detection, Schedule | |
| Audio | | |
| Audio compression | G.711A | |
| Two-way audio | - | |
| Network | | |
| Network interface | RJ-45 (10/100 Base-T) | |
| WiFi standart/Frequency,GHz | 802.11(b/g/n) / 2.4 | |
| Network functions | NiP/DDNS/IPFilter/Email/NTP/UPNP/FTP/RTSP | |
| Languages supported | English, Russian, Arabic, French, Polish, Romanian, Hungarian, Italian, Czech | |
| Default IP address | DHCP (Auto) | |
| Username | admin | |
| Password | Empty by default | |
| HTTP port | 80 | |
| ONVIF port | - | |
| RTSP port | - | |
| RTSP string | - | |
| Control port | 8880 | |
| Configuration software | - | |
| Monitoring program | Partizan WiFi KIT CMS | |
| Mobile software | Partizan Wifi KIT | |
| Protocol integration | - | |
| Interface | | |
| Display quality | 1920x1080; 1440x900; 1280x1024; 1280x720; 1024x768 | |
| Video inputs | - | |
| Video outputs | 1ch VGA, 1ch HDMI | |
| Audio inputs | - | |
| Audio outputs | 1 ch RCA | |
| Alarm inputs | - | |
| Alarm outputs | - | |
| PTZ control | Control PTZ device by network | |
| USB | 1xUSB 2.0 | |
| Internal SATA, (max. 4Tb) | 1 | |
| External SATA, (max. 4Tb) | - | |
| External eSATA, (max. 4Tb) | - | |
| Dimensions | | |
| Size, mm | 258x210x42 | |
| Weight, g | 900 | |
| Common | | |
| Power supply | DC, V/A | 12/2 |
| | PoE/Class | - |
| Housing material | Metal | |
| Front material | Plastic | |
| Operating temperature, °C | 0 - +50 | |
| Warranty, years | 3 | |



- WiFi IP camera
- 2.0 Mp resolution
- IP66 rating
- Weatherproof housing
- IR leds
- 3-Axis mounting

| IP Camera | | |
|-----------------------------|--------------|--|
| Image Sensor | | |
| Sensor | | 1/2.8" Full HD SOI |
| Pixel Size, µm | | 2.8x2.8 |
| Resolution, points@fps | Main stream | PAL: 1920x1080@25, 1280x720@25, 704x576@25 NTSC: 1920x1080@30, 1280x720@30, 704x576@30 |
| | Sub stream | PAL:704x576@25, 320x288@25, NTSC:704x576@30, 320x288@30 |
| Day/Night mode | | Auto/Color/Black&White |
| Sensitivity, Lux/Iris | | Color 0.01Lux@F1.2, Black/White: 0.001 Lux@F1.2 |
| Dynamic range WDR, dB | | 69 |
| S/N ratio, dB | | 39 |
| Video functions | | AEC, AGS, AWB, ABF, BLC, OSD, PrivacyMasks |
| Codec profile | H.264 | Baseline / Main / High |
| Exposure mode, s | Auto | 1/50-1/10000 |
| | Manual | 0.256-65.536 |
| Bitrate Type, kb/s | Constant | 1024-8192 |
| | Variable | Worst/Worse/General/Good/Better/Best |
| Lens | | |
| Focal length, mm | | 3.6 |
| Iris, F | | 1.4 |
| Angle of View, ° | Horizontal | 77 |
| | Vertical | 61 |
| lens Type | Aspherical | - |
| | Spherical | + |
| Lens mount | | M12 |
| Control | | - |
| IR LED | | |
| Distance, m | | Up to 30 |
| Number of LEDs, pcs. | | 3 array LED |
| Beam Spread, ° | | 60 |
| Wavelength, nm | | 850 |
| IR Cut Filter | | Auto |
| Network | | |
| Network Interface | | RJ-45 (10/100Base-T) |
| WiFi standart/Frequency,GHz | | 802.11(b/g/n) / 2.4 |
| Network functions | | Cloud/NIP/DDNS/IPFilter/E-mail/NTP/UPNP/RTSP |
| Languages supported | | English, Russian, Arabic, French, Poland, Romanian, Hungarian, Italian |
| Default IP address | | DHCP (Auto) |
| Username | | admin |
| Password | | Empty by default |
| HTTP port | | 80 |
| ONVIF port | | - |
| RTSP port | | - |
| RTSP string | | - |
| Control port | | 8880 |
| Configuration software | | - |
| Monitoring program | | Partizan WiFi KIT CMS |
| Mobile software | | Partizan Wifi KIT |
| Protocol integration | | - |
| Dimensions | | |
| Size, mm | Total length | 159 |
| | Housing | Ø82x159 |
| | Bracket | Ø85 |
| Weight, g | | 470 |
| Common | | |
| Power Supply | DC12V, A | 0.5 |
| | PoE, Class/W | - |
| Audio | | - |
| Housing material | | Metal |
| Bracket material | | Metal |
| IP rating | | 66 |
| IK rating | | - |
| Operating temperature, °C | | -40 - +60 |
| Warranty, years | | 3 |

Inside the Kit

| | |
|-----------------|---|
| WiFi NVR | 1 |
| WiFi IP cameras | 4 |
| Power supply | 5 |
| Mouse | 1 |
| Lan cable | 1 |
| WiFi antena | 5 |
| Mounting Kit | 1 |
| Manual | 1 |